

## High-Speed Pipe Cutter

- Quick cutting. Only 10 seconds to cut 60mm stainless steel pipe (EHC-60F).
- Clean cutting of mirror surface and plastic coated pipe with urethane rollers (EHC-60U).
- Free from outside burrs, metal chips and sparks from cutting.
- Vises are unnecessary for chucking pipes.
- Core reamer easily removes inside burrs. (optional accessory)
- Stable cutting for longer pipes with a Pipe Support (optional accessory).
- Cutter wheel tested to 100 cuts for 60mm stainless steel pipe.

### EHC-60F and 60U



EHC-60F



EHC-60U for plastic coated or mirror surface pipe with Pipe Support (optional accessory)

### Specifications

Cutting Capacity	Stainless Steel Pipe for general utility use (JIS G 3488 equivalent)	OD 16mm ~ 60.5mm Max wall thickness 1.5mm
	Copper Pipe for water supply (JWWAH101, JIS H 3300 equivalent)	OD 16mm ~ 54mm Max wall thickness 1.78mm
	Conduit Pipe without threads (JIS C 8305 equivalent)	OD 19mm ~ 51mm Max wall thickness 1.4mm
	Plastic coated pipe for handrails	OD 16mm ~ 60.5mm Max wall thickness 4.0mm Max metal wall thickness 1.5mm
Motor	Single phase series motor 350W AC240V 50/60Hz	
Measurements	250(L) x 210(W) x 330(H)	
Weight	11.5 kg	

### Optional Accessories

Pipe Support with Aluminum or Urethane rollers : EHCS-60 or EHCS-60U  
Core Reamer set (pre-assembled): EHCR-60ST